



**hydewa**<sup>®</sup>

# GLASBORD<sup>®</sup> - FRP SURFACES

FRP = (FIBRE REINFORCED PLASTIC)

## Application



Installations in the corridor area of a dairy

- Food processing
- Cold storage & warehouses
- Kitchens & Catering
- Healthcare (Hospitals, laboratories, clean rooms)
- Sanitary facilities
- Agriculture & Hobby



Surface	embossed	flat / smooth	Fire class*
Glasbord®PWI-P	2,3mm		B2 / E
Glasbord®PWI	3,0mm		B2/ E
Glasbord®FX-FM	2,3 mm/3mm		B1/ B-s2-d0
Glasbord®FS-FM		1,9 mm	B1/ B-s2-d0
Glasbord®PSI-F		1,9 mm	B2/ E
Glasbord®FX	1,9 mm		B1/ B-s1-d0

\*Fire class DIN EN 13501-01


Length: 2100, 2500, 2750, 3000, 3500 mm

Width: 1200 mm

Colours:



white  
(standard)



special colours above 1000 m<sup>2</sup> in RAL

## Features

- Surfaseal® film sealant
- Easy to clean, moisture resistant
- Hygienic, Aesthetic and visually appealing
- Cold resistant
- Food safe
- Chemical resistant, no attack surface for microorganisms
- Robust and durable
- Easy to install



## Direct mounting system\*

Material required:

- Hydewa special adhesive 600ml or 1800ml bag
- Hydewa Cleaner
- if necessary, primer (Hydewa Flex Primer 1210) for porous, absorbent substrates
- Installation accessories (notched trowel, pressure roller, joint puller, adhesive tape)
- Joint cover strip (H-strip)
- Corner strips

\*Please refer to our data sheets and installation instructions



Accessories - Direct fix

## Joints

For the joint, we recommend Hydewa hps-1c or Hydewa hps-2k joint sealant, which is injected using a joint press and then smoothed. It should be noted that under certain conditions (chemicals, smoke, etc.), joints may become discolored. However, as long as the joint remains physically intact, there is no need to replace it. Cracked or damaged joints can be replaced without any problems.

In the event of component movement (settlement, expansion behavior of the materials due to extreme climatic fluctuations, moisture, etc.), we recommend soft jointing with Hydewa hps-1c.



hps-1c sealant

## Certificates

- Fire classification (B-s1-d0, B-s2-d0, B2)
- Food safety certificate (surface & joint sealants)
- FM certification for Glasbord® FXFM 2.3 mm and FSFM 1.9 mm
- Greenguard Gold (very low emissions)
- HACCP



## We're pleased to help!

We would be pleased to assist you with our expertise.

## Do you have any suggestions?

In order to provide you, the customer, with consistently the products as well as our production plant are constantly being developed and improved.

If you have any questions or suggestions about our product, please contact:

Hydewa® GmbH · Hydewaplatz 1-3 ·  
D-95466 Weidenberg  
Tel. +49 (0)92 78 / 9 70-0  
Fax +49 (0)92 78 / 9 70-50  
info@hydewa.com · www.hydewa.com



Stand: 01.01.2024

